



**SAFETY DATA SHEET**

Form #: SDS 853020D  
 Revised: AA (06/16/2016)  
 Supersedes: 05/14/2015  
 ECO #: 1001735

**I. PRODUCT IDENTIFICATION**

**Chemical Trade Name (as used on label):**

Lead-Acid Battery, Wet

**Chemical Family/Classification:**

Electric Storage Battery

**Synonyms:**

Industrial Battery, Traction Battery, Stationary Battery,  
 Deep Cycle Battery

**Telephone:**

For information and emergencies, contact  
 1-800-211-3684

**Manufacturer's Name/Address:**

Douglas Battery  
 1255 Creekshire Way, Suite 221  
 Winston-Salem, NC 27103

**24-Hour Emergency Response Contact:**

CHEMTREC DOMESTIC: 800-424-9300 CHEMTREC INTL: 703-527-3877

**II. PHYSICAL HAZARDS IDENTIFICATION**

HEALTH	ENVIRONMENTAL	PHYSICAL
Acute Toxicity (Oral/Dermal/Inhalation) Category 4 Skin Corrosion/Irritation Category 1A Eye Damage Category 1 Reproductive Category 1A Carcinogenicity (lead compounds) Category 1B Carcinogenicity (arsenic) Category 1A Carcinogenicity (acid mist) Category 1A Specific Target Organ Category 2 Toxicity (repeated exposure)	Aquatic Chronic 1 Aquatic Acute 1	Explosive Chemical, Division 1.3

**GHS LABEL:**

HEALTH	ENVIRONMENTAL	PHYSICAL

**Hazard Statements**

**DANGER!**

Causes severe skin burns and serious eye damage.  
 May damage fertility or the unborn child if ingested or inhaled.  
 May cause cancer if ingested or inhaled.  
 Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure.  
 May form explosive air/gas mixture during charging.  
 Extremely flammable gas (hydrogen).  
 Explosive, fire, blast, or projection hazard.  
 May cause harm to breast-fed children  
 Harmful if swallowed, inhaled, or contact with skin  
 Causes skin irritation, serious eye damage.

**Precautionary Statements**

Wash thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Wear protective gloves/protective clothing, eye protection/face protection.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Use only outdoors or in a well-ventilated area.  
 Contact with internal components may cause irritation or severe burns. Avoid contact with internal acid.  
 Irritating to eyes, respiratory system, and skin.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood  
 Avoid contact during pregnancy/while nursing  
 Keep away from heat./sparks/open flames/hot surfaces. No smoking

**III. COMPOSITION AND INGREDIENTS**

Components	CAS Number	Approximate % by Wt.
<b>Inorganic Lead Compound:</b>		
Lead	7439-92-1	60-70
* Antimony	7440-36-0	2
* Arsenic	7440-38-2	0.2
* Calcium	7440-70-2	0.04
* Tin	7440-31-5	0.2
<b>Electrolyte (Sulfuric Acid (H2SO4/H2O))</b>	7664-93-9	10-30
<b>Case Material:</b>		5-10
Polypropylene	9003-07-0	
Polystyrene	9003-53-6	
Styrene Acrylonitrile	9003-54-7	
Acrylonitrile Butadiene Styrene	9003-56-9	
Styrene Butadiene	9003-55-8	
Polyvinylchloride	9002-86-2	
Polycarbonate, Hard Rubber, Polyethylene	9002-88-4	
<b>Other:</b>		
Silicon Dioxide (Gel batteries only)	7631-86-9	1-5
Sheet Molding Compound (Glass reinforced polyester)	---	

Inorganic lead and electrolyte (sulfuric acid) are the primary components of every battery manufactured by Douglas.  
 Other ingredients may be present dependent upon battery type. Contact your Douglas representative for additional information.

**IV. FIRST AID MEASURES**



# SAFETY DATA SHEET

Form #: SDS 853020D  
Revised: AA (06/16/2016)  
Supersedes: 05/14/2015  
ECO #: 1001735

## Inhalation:

**Sulfuric Acid:** Remove to fresh air immediately. If breathing is difficult, give oxygen. Consult a physician  
**Lead:** Remove from exposure, gargle, wash nose and lips; consult physician.

## Ingestion:

**Sulfuric Acid:** Give large quantities of water; do not induce vomiting or aspiration into the lungs may occur and can cause permanent injury or death; consult a physician.  
**Lead:** Consult physician immediately.

## Skin:

**Sulfuric Acid:** Flush with large amounts of water for at least 15 minutes; remove contaminated clothing completely, including shoes. If symptoms persist, seek medical attention. Wash contaminated clothing before reuse. Discard contaminated shoes.  
**Lead:** Wash immediately with soap and water.

## Eyes:

**Sulfuric Acid and Lead:** Flush immediately with large amounts of water for a least 15 minutes while lifting lids. Seek immediate medical attention if eyes have been exposed directly to acid.

## V. FIRE FIGHTING MEASURES

**Flash Point:** N/A

**Flammable Limits:** LEL = 4.1% (Hydrogen Gas)

UEL = 74.2%

**Extinguishing Media:** CO<sub>2</sub>; foam; dry chemical. Do not use carbon dioxide directly on cells. Avoid breathing vapors. Use appropriate media for surrounding fire.

### Special Fire Fighting Procedures:

If batteries are on charge, shut off power. Use positive pressure, self-contained breathing apparatus. Water applied to electrolyte generates heat and causes it to spatter. Wear acid-resistant clothing, gloves, face and eye protection.  
But note that strings of series connected batteries may still pose risk of electric shock even when charging equipment is shut down.

### Unusual Fire and Explosion Hazards:

Highly flammable hydrogen gas is generated during charging and operation of batteries. To avoid risk of fire or explosion, keep sparks or other sources of ignition away from batteries. Do not allow metallic materials to simultaneously contact negative and positive terminals of cells and batteries. Follow manufacturer's instructions for installation and service.

## VI. ACCIDENTAL RELEASE MEASURES

### Spill or Leak Procedures:

Stop flow of material, contain/absorb small spills with dry sand, earth, and vermiculite. Do not use combustible materials. If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc. Wear acid-resistant clothing, boots, gloves, and face shield. Do not allow discharge of unneutralized acid to sewer. Acid must be managed in accordance with local, state, and federal requirements. Consult state environmental agency and/or federal EPA.

## VII. HANDLING AND STORAGE

### Handling:

Unless involved in recycling operations, do not breach the casing or empty the contents of the battery. Handle carefully and avoid tipping, which may allow electrolyte leakage. There may be increasing risk of electric shock from strings of connected batteries.  
Keep containers tightly closed when not in use. If battery case is broken, avoid contact with internal components.  
Keep vent caps on and cover terminals to prevent short circuits. Place cardboard between layers of stacked automotive batteries to avoid damage and short circuits.  
Keep away from combustible materials, organic chemicals, reducing substances, metals, strong oxidizers and water. Use banding or stretch wrap to secure items for shipping.

### Storage:

Store batteries in cool, dry, well-ventilated areas with impervious surfaces and adequate containment in the event of spills. Batteries should also be stored under roof for protection against adverse weather conditions. Separate from incompatible materials. Store and handle only in areas with adequate water supply and spill control. Avoid damage to containers. Keep away from fire, sparks and heat. Keep away from metallic objects could bridge the terminals on a battery and create a dangerous short-circuit.

### Charging:

There is a possible risk of electric shock from charging equipment and from strings of series connected batteries, whether or not being charged. Shut-off power to chargers whenever not in use and before detachment of any circuit connections. Batteries being charged will generate and release flammable hydrogen gas. Charging space should be ventilated. Keep battery vent caps in position. Prohibit smoking and avoid creation of flames and sparks nearby. Wear face and eye protection when near batteries being charged.



**SAFETY DATA SHEET**

Form #: SDS 853020D  
 Revised: AA (06/16/2016)  
 Supersedes: 05/14/2015  
 ECO #: 1001735

**VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Exposure Limits (mg/m3) Note: N.E.= Not Established

INGREDIENTS (Chemical/Common Names)	OSHA PEL	ACGIH	US NIOSH	Quebec PEV	Ontario OEL	EU OEL
Lead and Lead Compounds (inorganic)	0.05	0.05	0.05	0.05	0.05	0.15 (b)
Antimony	0.5	0.5	0.5	0.5	0.5	0.5 (b,e)
Arsenic	0.01	0.01	0.002	0.2	0.01	N.E.
Calcium	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Tin	2	2	2	2	2	N.E.
Electrolyte (Sulfuric Acid)	1	0.2	1	1	0.2	N.E.
Polypropylene	N.E.	N.E.	N.E.	N.E.	N.E.	0.05 (c)
Polystyrene	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Styrene Acrylonitrile	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Acrylonitrile Butadiene						N.E.
Styrene	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Styrene Butadiene	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Polyvinylchloride	N.E.	N.E.	N.E.	N.E.	1	N.E.
Polycarbonate, Hard						N.E.
Rubber, Polyethylene	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Silicon Dioxide						N.E.
(Gel Batteries Only)	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.
Sheet Molding Compound (Glass reinforced polyester)	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.

**NOTES:**

- (b) As inhalable aerosol
- (c) Thoracic fraction
- (e) Based on OELs Of Austria, Belgium, Denmark, France, Netherlands, Switzerland, & U.K.

**Engineering Controls (Ventilation):**

Store and handle in well-ventilated area. If mechanical ventilation is used, components must be acid-resistant. Handle batteries cautiously to avoid spills. Make certain vent caps are on securely. Avoid contact with internal components. Wear protective clothing, eye and face protection when filling, charging or handling batteries. Do not allow metallic materials to simultaneously contact both the positive and negative terminals of the batteries. Charge the batteries in areas with adequate ventilation. General dilution ventilation is acceptable.

**Respiratory Protection (NIOSH/MSHA approved):**

None required under normal conditions. When concentrations of sulfuric acid mist are known to exceed the PEL, use NIOSH or MSHA-approved respiratory protection.

**Skin Protection:**

If battery case is damaged, use rubber or plastic acid-resistant gloves with elbow-length gauntlet, acid-resistant apron, clothing and boots.

**Eye Protection:**

If battery case is damaged, use chemical goggles or face shield.

**Other Protection:**

In areas where sulfuric acid is handled in concentrations greater than 1%, emergency eyewash stations and showers should be provided, with unlimited water supply. Acid-resistant apron. Under severe exposure emergency conditions, wear acid-resistant clothing and boots. Face shield recommended when adding water or electrolyte to batteries, wash hands after handling.

**IX. PHYSICAL AND CHEMICAL PROPERTIES**

Properties Listed Below are for Electrolyte:

<b>Boiling Point:</b>	203 - 240° F	<b>Specific Gravity (H<sub>2</sub>O = 1):</b>	1.215 to 1.350
<b>Melting Point:</b>	N/A	<b>Vapor Pressure (mm Hg):</b>	10
<b>Solubility in Water:</b>	100%	<b>Vapor Density (AIR = 1):</b>	Greater than 1
<b>Evaporation Rate: (Butyl Acetate = 1)</b>	Less than 1	<b>% Volatile by Weight:</b>	N/A
<b>pH:</b>	~1 to 2	<b>Flash Point:</b>	Below room temperature (as hydrogen gas)
<b>LEL (Lower Explosive Limit)</b>	4.1% (Hydrogen)	<b>UEL (Upper Explosive Limit)</b>	74.2% (Hydrogen)
<b>Appearance and Odor:</b>	Manufactured article; no apparent odor. Electrolyte is a clear liquid with a sharp, penetrating, pungent odor.		



# SAFETY DATA SHEET

Form #: SDS 853020D  
Revised: AA (06/16/2016)  
Supersedes: 05/14/2015  
ECO #: 1001735

## X. STABILITY AND REACTIVITY

Stability: Stable X Unstable

This product is stable under normal conditions at ambient temperature.

Conditions To Avoid: Prolonged overcharge; sources of ignition

### Incompatibility: (Materials to avoid)

**Sulfuric Acid:** Contact with combustibles and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulfur trioxide gas, strong oxidizers and water. Contact with metals may produce toxic sulfur dioxide fumes and may release flammable hydrogen gas.

**Lead Compounds:** Avoid contact with strong acids, bases, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen and reducing agents.

**Arsenic compounds:** strong oxidizers; bromine azide. NOTE: hydrogen gas can react with inorganic arsenic to form the highly toxic gas-arsine.

### Hazardous Decomposition Products:

**Sulfuric Acid:** Sulfur trioxide, carbon monoxide, sulfuric acid mist, sulfur dioxide, and hydrogen sulfide.

**Lead Compounds:** High temperatures likely to produce toxic metal fume, vapor, or dust; contact with strong acid or base or presence of nascent hydrogen may generate highly toxic arsine gas.

### Hazardous Polymerization:

Will not occur

## XI. TOXICOLOGICAL INFORMATION

### Routes of Entry:

**Sulfuric Acid:** Harmful by all routes of entry.

**Lead Compounds:** Hazardous exposure can occur only when product is heated, oxidized or otherwise processed or damaged to create dust, vapor or fume. The presence of nascent hydrogen may generate highly toxic arsine gas.

### Inhalation:

**Sulfuric Acid:** Breathing of sulfuric acid vapors or mists may cause severe respiratory irritation.

**Lead Compounds:** Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs.

### Ingestion:

**Sulfuric Acid:** May cause severe irritation of mouth, throat, esophagus and stomach.

**Lead Compounds:** Acute ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping. This may lead rapidly to systemic toxicity and must be treated by a physician.

### Skin Contact:

**Sulfuric Acid:** Severe irritation, burns and ulceration.

**Lead Compounds:** Not absorbed through the skin.

**Arsenic Compounds:** Contact may cause dermatitis and skin hyper pigmentation.

### Eye Contact:

**Sulfuric Acid:** Severe irritation, burns, cornea damage, and blindness.

**Lead Compounds:** May cause eye irritation.

### Effects of Overexposure - Acute:

**Sulfuric Acid:** Severe skin irritation, damage to cornea, upper respiratory irritation.

**Lead Compounds:** Symptoms of toxicity include headache, fatigue, abdominal pain, loss of appetite, muscular aches and weakness, sleep disturbances and irritability.

### Effects of Overexposure - Chronic:

**Sulfuric Acid:** Possible erosion of tooth enamel, inflammation of nose, throat and bronchial tubes.

**Lead Compounds:** Anemia; neuropathy, particularly of the motor nerves, with wrist drop; kidney damage; reproductive changes in males and females. Repeated exposure to lead and lead compounds in the workplace may result in nervous system toxicity. Some toxicologists report abnormal conduction velocities in persons with blood lead levels of 50mcg/100 ml or higher. Heavy lead exposure may result in central nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic) tissues.

### Carcinogenicity:

**Sulfuric Acid:** The International Agency for Research on Cancer (IARC) has classified "strong inorganic acid mist containing sulfuric acid" as a Group 1 carcinogen, a substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery. Inorganic acid mist (sulfuric acid mist) is not generated under normal use of this product. Misuse of the product, such as overcharging, may result in the generation of sulfuric acid mist.

**Lead Compounds:** Lead is listed as a Group 2A carcinogen, likely in animals at extreme doses. Per the guidance found in OSHA 29 CFR 1910.1200 Appendix F, this is approximately equivalent to GHS Category 1B. Proof of carcinogenicity in humans is lacking at present.

**Arsenic:** Arsenic is listed by IARC as a Group 1 - carcinogenic to humans. Per the guidance found in OSHA 29 CFR 1910.1200 Appendix F, this is approximately equivalent to GHS Category 1A.

### Medical Conditions Generally Aggravated by Exposure:

Overexposure to sulfuric acid mist may cause lung damage and aggravate pulmonary conditions. Contact of sulfuric acid with skin may aggravate diseases such as eczema and contact dermatitis. Lead and its compounds can aggravate some forms of kidney, liver and neurologic diseases.



# SAFETY DATA SHEET

Form #: SDS 853020D  
Revised: AA (06/16/2016)  
Supersedes: 05/14/2015  
ECO #: 1001735

## Acute Toxicity:

Inhalation LD50:

Electrolyte: LC50 rat: 375 mg/m<sup>3</sup>; LC50: guinea pig: 510 mg/m<sup>3</sup>

Elemental Lead: Acute Toxicity Point Estimate = 4500 ppmV (based on lead bullion)

Elemental Arsenic: No data

## Oral LD50:

Electrolyte: rat: 2140 mg/kg

Elemental Lead: Acute Toxicity Estimate (ATE) = 500 mg/kg body weight (based on lead bullion)

Elemental Arsenic: LD50 mouse: 145 mg/kg

Elemental Antimony: LD50 rat: 100 mg/kg

## Additional Health Data:

All heavy metals, including the hazardous ingredients in this product, are taken into the body primarily by inhalation and ingestion. Most inhalation problems can be avoided by adequate precautions such as ventilation and respiratory protection covered in Section 8. Follow good personal hygiene to avoid inhalation and ingestion: wash hands, face, neck and arms thoroughly before eating, smoking or leaving the worksite. Keep contaminated clothing out of non-contaminated areas, or wear cover clothing when in such areas. Restrict the use and presence of food, tobacco and cosmetics to non-contaminated areas. Work clothes and work equipment used in contaminated areas must remain in designated areas and never taken home or laundered with personal non-contaminated clothing. This product is intended for industrial use only and should be isolated from children and their environment.

The 19<sup>th</sup> Amendment to EC Directive 67/548/EEC classified lead compounds, but not lead in metal form, as possibly toxic to reproduction. Risk phrase 61: May cause harm to the unborn child, applies to lead compounds, especially soluble forms.

## XII. ECOLOGICAL INFORMATION

### Environmental Fate:

Lead is very persistent in soil and sediments. No data on environmental degradation. Mobility of metallic lead between ecological compartments is slow. Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants but little bioaccumulation occurs through the food chain. Most studies include lead compounds and not elemental lead.

### Environmental Toxicity: Aquatic Toxicity:

Sulfuric acid: 24-hr LC50, freshwater fish (Brachydanio rerio): 82 mg/L  
96 hr- LOEC, freshwater fish (Cyprinus carpio): 22 mg/L  
Lead: 48 hr LC50 (modeled for aquatic invertebrates): <1 mg/L, based on lead bullion  
Arsenic: 24 hr LC50, freshwater fish (Carrassius auratus) >5000 g/L.

### Additional Information:

- No known effects on stratospheric ozone depletion.
- Volatile organic compounds: 0% (by Volume)
- Water Endangering Class (WGK): NA

## XIII. DISPOSAL CONSIDERATIONS (GENERAL STATES)

Spent batteries: Send to secondary lead smelter for recycling. Spent lead-acid batteries are not regulated as hazardous waste when the requirements of 40 CFR Section 266.80 are met. This should be managed in accordance with approved local, state and federal requirements. Consult state environmental agency and/or federal EPA.

### Electrolyte:

Place neutralized slurry into sealed containers and handle as applicable with state and federal regulations. Large water-diluted spills, after neutralization and testing, should be managed in accordance with approved local, state and federal requirements. Consult state environmental agency and/or federal EPA.

Following local, State/Provincial, and Federal/National regulations applicable to end-of-life characteristics will be the responsibility of the end-user.

## XIV. TRANSPORT INFORMATION

### U.S. DOT:

The transportation of wet and moist charged (moist active) batteries within the continental United States is regulated by the U.S. DOT through the Code of Federal Regulations, Title 49 (49CFR). These regulations classify these types of batteries as a hazardous material. Refer to CFR 49, 173.159 for more details pertaining to the transportation of wet and moist batteries.

#### The shipping information is as follows:

Proper Shipping Name: Batteries, wet, filled with acid  
Hazardous Class: 8  
UN Identification: UN2794

Packing Group: N/A  
Label/Placard Required: Corrosive

Contact your Douglas representative for additional information regarding the classification of batteries.

49 CFR 173.159(e) specifies that when transported by highway or rail, electric storage batteries containing electrolyte or corrosive battery fluid are not subject to any other requirements of this subchapter, if all of the following are met:

- (1) No other hazardous materials may be transported in the same vehicle;
- (2) The batteries must be loaded or braced so as to prevent damage and short circuits in transit;
- (3) Any other material loaded in the same vehicle must be blocked, braced, or otherwise secured to prevent contact with or damage to the batteries; and
- (4) The transport vehicle may not carry material shipped by any person other than the shipper of the batteries.

If any of the above-referenced requirements are not met, the batteries must be shipped as fully-regulated Class 8 Corrosive hazardous materials.



**SAFETY DATA SHEET**

Form #: SDS 853020D  
 Revised: AA (06/16/2016)  
 Supersedes: 05/14/2015  
 ECO #: 1001735

**IATA Dangerous Goods Regulations DGR:**

The international transportation of wet and moist charged (moist active) batteries is regulated by the International Air Transport Association (IATA). These regulations also classify these types of batteries as a hazardous material. The batteries must be packed according to IATA Packing Instruction 870.

The shipping information is as follows:

Proper Shipping Name: Batteries, wet, filled with acid	Packing Group: N/A
Hazardous Class: 8	Label/Placard Required: Corrosive
UN Identification: UN2794	

Contact your Douglas representative for additional information regarding the classification of batteries.

**IMDG:**

The international transportation of wet and moist charged (moist active) batteries is regulated by the International Maritime Dangerous Goods code (IMDG). These regulations also classify these types of batteries as hazardous material. The batteries must be packed according to IMDG code pages 8120 and 8121. IMDG Code Packing Instruction P801.

The shipping information is as follows:

Proper Shipping Name: Batteries, wet, filled with acid	Packing Group: N/A
Hazardous Class: 8	Label/Placard Required: Corrosive
UN Identification: UN2794	

Contact your Douglas representative for additional information regarding the classification of batteries.

**XV. REGULATORY INFORMATION**

**UNITED STATES:**

**EPA SARA Title III:**

**Section 302 EPCRA Extremely Hazardous Substances (EHS):**

Sulfuric acid is a listed "Extremely Hazardous Substance" under EPCRA, with a Threshold Planning Quantity (TPQ) of 1,000 lbs. EPCRA Section 302 notification is required if 1000 lbs or more of sulfuric acid is present at one site (40 CFR 370.10). For more information consult 40 CFR Part 355. The quantity of sulfuric acid will vary by battery type. Contact your Douglas representative for additional information.

**Section 304 CERCLA Hazardous Substances:**

Reportable Quantity (RQ) for spilled 100% sulfuric acid under CERCLA (Superfund) and EPCRA (Emergency Planning and Community Right to Know Act) is 1,000 lbs. State and local reportable quantities for spilled sulfuric acid may vary.

**Section 311/312 Hazard Categorization:**

EPCRA Section 312 Tier Two reporting is required for non-automotive batteries if sulfuric acid is present in quantities of 500 lbs or more and/or if lead is present in quantities of 10,000 lbs or more. For more information consult 40 CFR 370.10 and 40 CFR 370.40.

**Section 313 EPCRA Toxic Substances:**

40 CFR section 372.38 (b) states: If a toxic chemical is present in an article at a covered facility, a person is not required to consider the quantity of the toxic chemical present in such article when determining whether an applicable threshold has been met under § 372.25, § 372.27, or § 372.28 or determining the amount of release to be reported under § 372.30. This exemption applies whether the person received the article from another person or the person produced the article. However, this exemption applies only to the quantity of the toxic chemical present in the article.

**Supplier Notification:**

This product contains toxic chemicals, which may be reportable under EPCRA Section 313 Toxic Chemical Release Inventory (Form R) requirements. If you are a manufacturing facility under SIC codes 20 through 39, the following information is provided to enable you to complete the required reports:

<u>Toxic Chemical</u>	<u>CAS Number</u>	<u>Approximate % by Wt.</u>
Lead	7439-92-1	60
Electrolyte (Sulfuric Acid (H2SO4/H2O))	7664-93-9	10 - 30
* Antimony	7440-36-0	2
* Arsenic	7440-38-2	0.2
Tin	7440-31-5	0.2

See 40 CRG Part 370 for more details.

If you distribute this product to other manufacturers in SIC Codes 20 through 39, this information must be provided with the first shipment of each calendar year.

The Section 313 supplier notification requirement does not apply to batteries, which are "consumer products".

\* Not present in all battery types. Contact your Douglas representative for additional information.



# SAFETY DATA SHEET

Form #: SDS 853020D  
Revised: AA (06/16/2016)  
Supersedes: 05/14/2015  
ECO #: 1001735

**TSCA:**

TSCA Section 8b – Inventory Status: All chemicals comprising this product are either exempt or listed on the TSCA Inventory.

TSCA Section 12b (40 CFR Part 707.60(b)) No notice of export will be required for articles, except PCB articles, unless the Agency so requires in the context of individual section 5, 6, or 7 actions.

TSCA Section 13 (40 CFR Part 707.20): No import certification required (EPA 305-B-99-001, June 1999, Introduction to the Chemical Import Requirements of the Toxic Substances Control Act, Section IV.A).

**RCRA:**

Spent Lead Acid Batteries are subject to streamlined handling requirements when managed in compliance with 40 CFR section 266.80 or 40 CFR part 273. Waste sulfuric acid is a characteristic hazardous waste; EPA hazardous waste number D002 (corrosivity) and D008 (lead).

**CAA:**

Douglas supports preventative actions concerning ozone depletion in the atmosphere due to emissions of CFC's and other ozone depleting chemicals (ODC's), defined by the USEPA as Class I substances. Pursuant to Section 611 of the Clean Air Act Amendments (CAAA) of 1990, finalized on January 19, 1993, Douglas established a policy to eliminate the use of Class I ODC's prior to the May 15, 1993 deadline.

**STATE REGULATIONS (US):**

**Proposition 65:**  
Warning: Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. Wash hands after handling.

**INTERNATIONAL REGULATIONS:**

Distribution into Quebec to follow Canadian Controlled Product Regulations (CPR) 24(1) and 24(2).

Distribution into the EU to follow applicable Directives to the Use, Import/Export of the product as-sold.

**XVI. OTHER INFORMATION**

Revised: AA (06/16/2016)

**NFPA Hazard Rating for Sulfuric Acid:**

Flammability (Red) = 0  
Health (Blue) = 3

Reactivity (Yellow) = 2  
Sulfuric acid is water-reactive if concentrated.

**DISCLAIMER**

This Safety Data Sheet is created by the manufacturer to comply with the requirements of 29 CFR 1910.1200. To the extent allowed by law, the manufacturer hereby expressly disclaims any liability to any third party, including users of this product, including, but not limited to, consequential or other damages, arising out of the use of, or reliance on, this Safety Data Sheet.

