Elanco

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or

Clinafarm Spray

designation of the mixture

Registration number

-

Synonyms

None.

Item Code

MN0812

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Biocidal product

Uses advised against

None known,

1.3. Details of the supplier of the safety data sheet

Supplier

Company name

Elanco Animal Health

Address

2500 Innovation Way

Greenfield, IN 46140 United States

Division

Eli Lilly and Company

Telephone

Phone:

lilly_msds@lilly.com

e-mail
1.4. Emergency telephone

CHEMTREC:

00+1+703-527-3887 (24 hours)

+1-317-276-2000

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification

R10, Xn;R20/22, Xì;R38-41, N;R51/53

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids

Category 3

H226 - Flammable liquid and

vapour.

Health hazards

Acute toxicity, oral

Category 4

H302 - Harmful if swallowed.

Acute toxicity, inhalation

Category 4

H332 - Harmful if inhaled.

Skin corrosion/irritation

Category 2

H315 - Causes skin irritation.

Serious eye damage/eye irritation

Category 1

H318 - Causes serious eye damage.

Environmental hazards
Hazardous to the aquatic environment,

long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with

long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

Benzyl alcohol, ENILCONAZOLE, Ethanol

Hazard pictograms

Signal word

Danger

Hazard statements

H226

Flammable liquid and vapour.

Material name: Clinafarm Spray

Revision date: 05-February-2014

Issue date: 04-June-2012

Supersedes date: 27-November-2012

SDS EU

H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/eye protection/face protection.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P273 Avoid release to the environment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

2.3. Other hazards No Chemical Safety Assessment has been carried out.

SECTION 3: Composition/information on ingredients

None.

3.2. Mixtures

General Information

Chemical name % CAS-No. / EC No. REACH Registration No. INDEX No. Notes

Docusate Sodium Solution 25 - 50 Mixture

Classification: DSD: F;R11, Xi;R36/38, R53

CLP: Flam. Liq. 2;H225, Skin Irrit. 2;H315, Eye Irrit. 2;H319

Ethanol 10 - 20 64-17-5 - 603-002-00-5

200-578-6

Classification: DSD: F;R11, Xi;R36

CLP: Flam. Liq. 2;H225, Eye Irrit. 2;H319

ENILCONAZOLE 20 - 25 35554-44-0 - 613-042-00-5

252-615-0

Classification: DSD: Xn;R20/22, Xi;R41, N;R50/53

CLP: Acute Tox. 4;H302, Eye Dam. 1;H318, Acute Tox. 4;H332, Acute Tox.

4;H332, Aquatic Acute 1;H400, Aquatic Chronic 1;H410

Benzyl alcohol 10 - 20 100-51-6 503-057-00-5

202-859-9 **Classification: DSD:** Xn;R20/22, Xi;R36

CLP: Acute Tox. 4;H302, Eye Irrit. 2;H319, Acute Tox. 4;H332

Other components below reportable levels 10 - < 20

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

Composition comments The full text for all R- and H-phrases is displayed in section 16.

SECTION 4: First aid measures

General information In the case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

Material name: Clinafarm Spray

Material name: Clinafarm Spray

SDS EU
Version No.: 03 Revision date: 05-February-2014 Issue date: 04-June-2012 Supersedes date: 27-November-2012 2 / 12

4.1. Description of first aid measures

Inhalation Oxygen or artificial respiration if needed. Get medical attention immediately.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and

shoes. Get medical attention immediately.

Eye contact In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Get medical attention immediately.

Ingestion Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having

convulsions. Call a physician or poison control centre immediately,

4.2. Most important symptoms and effects, both Eye irritation. Skin irritation.

acute and delayed 4.3. Indication of any

immediate medical attention

and special treatment

Not available.

needed

SECTION 5: Firefighting measures

General fire hazards

Not available.

5.1. Extinguishing media

Suitable extinguishing

Water mist. Dry powder. Foam. Carbon dioxide (CO2). Sand.

Unsuitable extinguishing

media

Not available.

5.2. Special hazards arising from the substance or

Hazardous decomposition products formed under fire conditions.

mixture 5.3. Advice for firefighters

> Special protective equipment for firefighters

Wear self-contained breathing apparatus and protective clothing.

Special fire fighting

procedures

Not available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Rubber or plastic apron.

Respirator with a full face mask.

ABEK P3

For emergency responders

Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental

precautions

Prevent spilled material from flowing onto adjacent land or into streams, ponds, or lakes. Avoid

discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Prevent further migration into the environment. Remove sources of ignition, Use

absorbent/adsorbent material to solidify liquids. Collect in a non-combustible container for prompt disposal. Local authorities should be advised if significant spillages cannot be contained. Large spills due to traffic accidents, etc., should be reported immediately to CHEMTREC and Elanco Animal

Health for assistance.

6.4, Reference to other sections

Refer to Sections 8, 11, 12 and 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Avoid breathing vapours or mists of this product, Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Keep away from heat and sources of ignition.

All equipment used when handling the product must be grounded.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames and high temperatures. Avoid contact with oxidising agents.

Do not store in open or unlabelled containers.

7.3. Specific end use(s) Not available.

Material name: Clinafarm Spray SDS EU Version No.: 03 Revision date: 05-February-2014 Issue date: 04-June-2012 Supersedes date: 27-November-2012 3 / 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components Type	Belgium. Exposure Limit Values. Components Type Value Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Components Type Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Value Benzyl alcohol (CAS TWA 5 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Value Benzyl alcohol (CAS TWA 1000 mg/m3 1000 ppm Bethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm 1000	Austria. MAK List, OEL Ordinal Components	Type	Value
MAK 1900 mg/m3 1000 ppm	MAK 1900 mg/m3 1000 ppm	Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3
Belgium. Exposure Limit Values. Components Type Value Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical sin France, INRS ED 984 to mp/m3 Finland, Workplace Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 1000 ppm	Belgium. Exposure Limit Values. Components Type Value Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical sin France, INRS ED 984 to mp/m3 Finland, Workplace Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 1000 ppm			2000 ppm
Belgium. Exposure Limit Values. Components Type Value Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at workers against risks of exposure to chemical in France, INRS ED 984 to components Type Value	Belgium. Exposure Limit Values. Components Type Value Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at workers against risks of exposure to chemical in France, INRS ED 984 to components Type Value		MAK	1900 mg/m3
Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical single properties against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure against risks of exposure against risks of exposure against risks o	Ethanol (CAS 64-17-5) TWA 1907 mg/m3 1000 ppm Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical single properties against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure to chemical agents at workers against risks of exposure against risks of exposure against risks of exposure against risks o			1000 ppm
Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work of components Benzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 40 mg/m3 1000 mg/m3 100	Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work of components Benzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 40 mg/m3 1000 mg/m3 100	-	_	Value
Bulgaria, OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Components Type Benzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Czech Republic, OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 1000 mg/m3 Czech Republic, OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 40 mg/m3 1000 mg/m3 1	Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Components Type Benzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 40 mg/m3 1000 mg/m3 1	Ethanol (CAS 64-17-5)	TWA	1007 mg/m2
Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 64-17-5) TWA 40 mg/m3 Celling 3000 mg/m3 TWA 40 mg/m3 Celling 3000 mg/m3 TWA 1000 mg/m3 Ethanol (CAS 64-17-5) TWA 40 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Serzyl alcohol (CAS 100 ppm TWA 45 mg/m3 (00-51-6) TWA 45 mg/m3 TWA 1900 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1	Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at wor Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 64-17-5) TWA 40 mg/m3 Celling 3000 mg/m3 TWA 40 mg/m3 Celling 3000 mg/m3 TWA 1000 mg/m3 Ethanol (CAS 64-17-5) TWA 40 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Serzyl alcohol (CAS 100 ppm TWA 45 mg/m3 (00-51-6) TWA 45 mg/m3 TWA 1900 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1	Ethanol (CAS 04-17-3)	IVA	=:
Benzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 40 mg/m3 Ethanol (CAS 64-17-5) TWA 40 mg/m3 Ethanol (CAS 64-17-5) TWA 1000 mg/m3 1000 mg/m3 TWA 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 Esteptember 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 ppm TWA 1000 mg/m3 500 ppm Finland, Workplace Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland, Workplace Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm Finland, Workplace Exposure Limits Components Type Value Ethanol (CAS 64-17-5) VIA 1900 mg/m3 1900 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3	Benzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA 1000 mg/m3 Czech Republic. OELs. Government Decree 361 Components Type Value Benzyl alcohol (CAS 100-51-6) TWA 40 mg/m3 Ethanol (CAS 64-17-5) TWA 40 mg/m3 Ethanol (CAS 64-17-5) TWA 1000 mg/m3 1000 mg/m3 TWA 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 Esteptember 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 ppm TWA 1000 mg/m3 500 ppm Finland, Workplace Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland, Workplace Exposure Limits Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm Finland, Workplace Exposure Limits Components Type Value Ethanol (CAS 64-17-5) VIA 1900 mg/m3 1900 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3	Bulgaria. OELs. Regulation No Components	13 on protection of workers a	gainst risks of exposure to chemical agents at wo
100-51-6 TWA	100-51-6 TWA			
Ethanol (CAS 64-17-5) TWA 1000 mg/m3	Ethanol (CAS 64-17-5) TWA 1000 mg/m3		IWA	5 mg/m3
Czech Republic. OELs. Government Decree 361 Components Type Value	Czech Republic. OELs. Government Decree 361 Components Type Value	2	TWA	1000 mg/m3
Components Type Value Benzyl alcohol (CAS Celling 80 mg/m3 100-51-6) TWA	Components Type Value Benzyl alcohol (CAS Celling 80 mg/m3 100-51-6) TWA	, ,		1000 mg/m3
Benzyl alcohol (CAS Celling 80 mg/m3 100-51-6 TWA 40 mg/m3 3000 mg/m3 TWA 1000 mg/m3 1000 pgm 1000	Benzyl alcohol (CAS Celling 80 mg/m3 100-51-6 TWA 40 mg/m3 3000 mg/m3 TWA 1000 mg/m3 1000 pgm 1000	-		Value
Ethanol (CAS 64-17-5) Ethanol (CAS 64-17-5) Ethanol (CAS 64-17-5) TWA Ceiling 3000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 pmm Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1WA 1000 mg/m3 500 ppm 1WA 1000 mg/m3 500 ppm TWA 1000 mg/m3 500 ppm TWA 45 mg/m3 Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm 10 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components WE Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm	Ethanol (CAS 64-17-5) Ethanol (CAS 64-17-5) Ethanol (CAS 64-17-5) TWA Ceiling 3000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 mg/m3 1000 pmm Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1WA 1000 mg/m3 500 ppm 1WA 1000 mg/m3 500 ppm TWA 1000 mg/m3 500 ppm TWA 45 mg/m3 Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm 10 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components WE Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm		уре	
Ethanol (CAS 64-17-5) Ceiling TWA 1000 mg/m3 TWA 1000 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components VME 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Components Type Value Sthanol (CAS 64-17-5) Type Value Sthanol (CAS 64-17-5) Type Value Sthanol (CAS 64-17-5) Type Value	Ethanol (CAS 64-17-5) Ceiling TWA 1000 mg/m3 TWA 1000 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components VME 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Components Type Value Sthanol (CAS 64-17-5) Type Value Sthanol (CAS 64-17-5) Type Value Sthanol (CAS 64-17-5) Type Value	,	Ceiling	80 mg/m3
TWA 1000 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Exposure CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemical type Type Value Exposure to Chemical type Type Value Exposure to Chemical type Type Value Exposure to Chem	TWA 1000 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 Exposure Limits Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Exposure CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemicals in France, INRS ED 984 Components Type Value Exposure to Chemical type Type Value Exposure to Chemical type Type Value Exposure to Chemical type Type Value Exposure to Chem		TWA	40 mg/m3
TWA 1000 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Serzyl alcohol (CAS TWA 45 mg/m3 TWA 45 mg/m3 TWA 1000 mg/m3 1000 ppm TWA 100 mg/m3 1000 ppm TWA 1000 mg/m3 1000 ppm Trance. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Type Walue Stanol (CAS 64-17-5) VLE 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm Tomponents Type Value Stanol (CAS 64-17-5) Type Value	TWA 1000 mg/m3 Denmark. Exposure Limit Values Components Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Serzyl alcohol (CAS TWA 45 mg/m3 TWA 45 mg/m3 TWA 1000 mg/m3 1000 ppm TWA 100 mg/m3 1000 ppm TWA 1000 mg/m3 1000 ppm Trance. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Type Walue Stanol (CAS 64-17-5) VLE 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm Tomponents Type Value Stanol (CAS 64-17-5) Type Value	Ethanol (CAS 64-17-5)	Ceiling	3000 mg/m3
Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 64-17-5) STEL 2500 mg/m3 300 ppm TWA 45 mg/m3 Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Velue 9500 mg/m3 1000 ppm VME 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm	Type Value Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 64-17-5) STEL 2500 mg/m3 300 ppm TWA 45 mg/m3 Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Velue 9500 mg/m3 1000 ppm VME 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm		TWA	
Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland, Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 100-51-6) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Stanol (CAS 64-17-5) VLE 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm	Ethanol (CAS 64-17-5) TLV 1900 mg/m3 1000 ppm Estonia, OELs, Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland, Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 100-51-6) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Stanol (CAS 64-17-5) VLE 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm	Denmark. Exposure Limit Valu	es	-
Estonia, OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS TWA 45 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components VLE 9500 mg/m3 1000 ppm TWE 1900 mg/m3 1000 ppm TYPE Value Sermany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Type Value Sthanol (CAS 64-17-5) Type Value	Estonia, OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS TWA 45 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components VLE 9500 mg/m3 1000 ppm TWE 1900 mg/m3 1000 ppm TYPE Value Sermany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Type Value Sthanol (CAS 64-17-5) Type Value	-		Value
Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 100 ppm TWA 45 mg/m3 100 ppm 100 mg/m3 100 ppm 100 mg/m3 100 ppm 100 mg/m3 100 ppm	Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 100 ppm TWA 45 mg/m3 100 ppm 100 mg/m3 100 ppm 100 mg/m3 100 ppm 100 mg/m3 100 ppm	Ethanol (CAS 64-17-5)	TLV	1900 mg/m3
Estonia, OELs, Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 1000 mg/m3 500 ppm 1000 mg/m3 1000-51-6) Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm 1000 ppm 1	Estonia, OELs, Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001) Components Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 1000 mg/m3 500 ppm 1000 mg/m3 1000-51-6) Ethanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm 1000			-
Type Value Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 1WA 45 mg/m3 100 ppm 100 ppm 10 ppm 10 ppm 10 ppm 10 ppm 10 ppm 100 ppm 100 ppm 10 ppm 10 ppm 100 ppm 1000 ppm	Type Value September 2001) Components Type Value Stanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS TWA 45 mg/m3 100-51-6) STEL 2500 mg/m3 1300 ppm 1000 ppm TWA 1900 mg/m3 1000 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm Sermany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Components Type Value Sthanol (CAS 64-17-5) Type Value Sthanol (CAS 64-17-5) Type Value	Estonia, OELs, Occupational Ex	posure Limits of Hazardous S	• •
Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm TWA Senzyl alcohol (CAS TWA STEL STOR STEL STEL STEL STOR STEL STEL STEL STOR STEL STOR STEL STOR STEL STOR STEL STOR STEL STOR STEL STEL STOR STOR STOR STEL STOR ST	Ethanol (CAS 64-17-5) STEL 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm TWA Senzyl alcohol (CAS TWA STEL STOR STEL STEL STEL STOR STEL STEL STEL STOR STEL STOR STEL STOR STEL STOR STEL STOR STEL STOR STEL STEL STOR STOR STOR STEL STOR ST	September 2001)		and the state of t
TWA 1000 ppm 1000 mg/m3 500 ppm Type Value Senzyl alcohol (CAS 100-51-6) Sthanol (CAS 64-17-5) TWA 45 mg/m3 100 ppm 100 ppm 100 ppm 1000 mg/m3 100-51-6) TWA 45 mg/m3 100 ppm 1000 ppm 1	TWA 1000 ppm 1000 mg/m3 500 ppm Type Value Senzyl alcohol (CAS 100-51-6) Sthanol (CAS 64-17-5) TWA 45 mg/m3 100 ppm 100 ppm 100 ppm 1000 mg/m3 100-51-6) TWA 45 mg/m3 100 ppm 1000 ppm 1	Components	Туре	Value
TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Benzyl alcohol (CAS (AS (AS (AS (AS (AS (AS (AS (AS (AS (TWA 1000 mg/m3 500 ppm Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS (AS (AS (AS (AS (AS (AS (AS (AS (AS (Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 100-51-6) Cithanol (CAS 64-17-5) TWA TWA TWA TWA TWA TWA TWA TW	Finland. Workplace Exposure Limits Components Type Value Senzyl alcohol (CAS 100-51-6) Ethanol (CAS 64-17-5) TWA TWA TWA 10 ppm 2500 mg/m3 1300 ppm 1900 mg/m3 1000 ppm 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Ethanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Ethanol (CAS 64-17-5) Type Value Ethanol (CAS 64-17-5) Type Value			1000 ppm
Type Value Senzyl alcohol (CAS (CAS (CAS (CAS (CAS (CAS (CAS (CAS	Type Value Senzyl alcohol (CAS (CAS (CAS (CAS (CAS (CAS (CAS (CAS		TWA	
Type Value Senzyl alcohol (CAS (CAS (CAS (CAS (CAS (CAS (CAS (CAS	Type Value Senzyl alcohol (CAS (CAS (CAS (CAS (CAS (CAS (CAS (CAS			500 ppm
Components Type Value Senzyl alcohol (CAS 3.00-51-6) STEL 10 ppm 10 ppm 1300 ppm 1300 ppm 1400 mg/m3 1000 ppm 1500 ppm	Components Type Value Senzyl alcohol (CAS 3.00-51-6) STEL 10 ppm 10 ppm 1300 ppm 1300 ppm 1400 mg/m3 1000 ppm 1500 ppm	inland. Workplace Exposure L	imits	• •
Renzyl alcohol (CAS (CAS (CAS (CAS (CAS (CAS (CAS (CAS	Renzyl alcohol (CAS (CAS (CAS (CAS (CAS (CAS (CAS (CAS			Value
thanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Components Type Value Strand (CAS 64-17-5) Type Value Strand (CAS 64-17-5) TWA 960 mg/m3	thanol (CAS 64-17-5) STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Components Type Value Strand (CAS 64-17-5) Type Value Strand (CAS 64-17-5) TWA 960 mg/m3	Ponzyl alcohol (CAC		45
Ethanol (CAS 64-17-5) STEL 100 ppm 2500 mg/m3 1300 ppm 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Sthanol (CAS 64-17-5) Type Value Sthanol (CAS 64-17-5) TWA 960 mg/m3	Ethanol (CAS 64-17-5) STEL 100 ppm 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Type Value Sthanol (CAS 64-17-5) TWA 960 mg/m3		IVVA	45 mg/m3
STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Sthanol (CAS 64-17-5) TWA 960 mg/m3	STEL 2500 mg/m3 1300 ppm TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Sthanol (CAS 64-17-5) TWA 960 mg/m3	,		10 ppm
TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Ethanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3	TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Ethanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3	thanol (CAS 64-17-5)	STEL	**
TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Ethanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3	TWA 1900 mg/m3 1000 ppm France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Ethanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Ethanol (CAS 64-17-5) TWA 960 mg/m3	Ellianor (Grad of 17 3)		- -
France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Thanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Thanol (CAS 64-17-5) TWA 960 mg/m3	France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value Thanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Thanol (CAS 64-17-5) TWA 960 mg/m3		TWA	
Trance. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Type Value Thanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Type Value Thanol (CAS 64-17-5) TWA 960 mg/m3	Trance. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Type Value Thanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Type Value Thanol (CAS 64-17-5) TWA 960 mg/m3			- -
Components Type Value Other Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	Components Type Value Other Sthanol (CAS 64-17-5) VLE 9500 mg/m3 5000 ppm VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	irance Threshold Limit Values	(VI ED) for Occupational Face	• •
VME 1900 ppm 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	VME 1900 ppm 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3			
VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	VME 1900 mg/m3 1000 ppm Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	Ethanol (CAS 64-17-5)	VLE	9500 mg/m3
Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3			5000 ppm
Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3		VME	• •
Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value Sthanol (CAS 64-17-5) TWA 960 mg/m3	Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG) Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3			-
Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	Components Type Value thanol (CAS 64-17-5) TWA 960 mg/m3	Germany. DFG MAK List (advise Compounds in the Work Area (ory OELs). Commission for the	• •
thanol (CAS 64-17-5) TWA 960 mg/m3	thanol (CAS 64-17-5) TWA 960 mg/m3	-	•	Value
		_	4 F *	
	500 ppm	#===! (CAC E4 17 E)		

Material name: Clinafarm Spray

Version No.: 03 Revision date: 05-February-2014 Issue date: 04-June-2012 Supersedes date: 27-November-2012 4 / 12

Germany. TRGS 900, Limit Values in to Components	Туре	Value
Ethanol (CAS 64-17-5)	AGW	960 mg/m3 500 ppm
Greece. OELs (Decree No. 90/1999, as	s amended)	.,
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Hungary. OELs. Joint Decree on Chem Components	ical Safety of Workplaces Type	Value
Ethanol (CAS 64-17-5)	STEL	7600 mg/m3
	TWA	1900 mg/m3
Iceland. OELs. Regulation 154/1999 o Components	n occupational exposure limits Type	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm
Ireland. Occupational Exposure Limits	1	2000 pp.11
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Italy. Occupational Exposure Limits		••
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm
Latvia. OELs. Occupational exposure li		
Components	Type	Value
Benzyl alcohol (CAS 100-51-6)	TWA	5 mg/m3
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Lithuania. OELs. Limit Values for Cher	nical Substances, General Requir	- -
Components	Туре	Value
Benzyl alcohoi (CAS	TWA	5 mg/m3
100-51-6) Ethanoi (CAS 64-17-5)	STEL	1000 / 2
Edianor (CAS 04-17-3)	SIEL	1900 mg/m3 1000 ppm
	TWA	1000 mg/m3
		500 ppm
Netherlands, OELs (binding)	T.m.s	Mark .
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL TWA	1900 mg/m3
Norway. Administrative Norms for Con		260 mg/m3
Components	Type	Value
Ethanol (CAS 64-17-5)	TLV	950 mg/m3
		500 ppm
Poland. MACs. Minister of Labour and S	Social Policy Regarding Maximun	n Allowable Concentrations and Intensi
in Working Environment		
Components	Туре	Value
Benzyl alcohol (CAS 100-51-6)	TWA	240 mg/m3
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
Portugal. VLEs. Norm on occupational	exposure to chemical agents (NP	2,
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1000 ppm
Romania. OELs. Protection of workers		*
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	9500 mg/m3
		5000 ppm

Components	Туре	Value
	TWA	1900 mg/m3
		1000 ppm
Slovakia. OELs, Regulation No.	. 300/2007 concerning protec	tion of health in work with chemical agents
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3
		1000 ppm
	TWA	960 mg/m3
		500 ppm
Slovenia, OELs, Regulations co	ncerning protection of worke	ers against risks due to exposure to chemicals while
working (Official Gazette of th	e Republic of Slovenia)	
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Spain, Occupational Exposure	Limits	
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1910 mg/m3
		1000 ppm
Sweden. Occupational Exposui	re Limit Values	
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
,		1000 ppm
	TWA	1000 mg/m3
		500 ppm
Switzerland. SUVA Grenzwerte	am Arbeitsplatz	••
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3
		1000 ppm
	TWA	960 mg/m3
	• •	500 ppm
JK, EH40 Workplace Exposure	Limits (WFLs)	Fr
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1920 ma/m3
::nanor (CAS 64-17-5)	IVVA	1970 00000

Biological limit values

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time
Benzyl alcohol (CAS 100-51-6)	25 %	red blood cell or total blood acetylcholineste rase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*
Ethanol (CAS 64-17-5)	25 %	red blood cell or total blood acetylcholineste rase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*

^{* -} For sampling details, please see the source document.

Recommended monitoring

procedures

Supplier: 0.125 mg/m3 TWA 8 hour (Enilconazole) A Lilly exposure guideline has not been established. The above exposure guideline has been

established by the supplier.

Derived no-effect level (DNEL)

Not available.

Material name: Clinafarm Spray

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Open handling is not recommended. Use appropriate control measures such as fume hood,

ventilated enclosure, local exhaust ventilation, or down-draft booth.

Individual protection measures, such as personal protective equipment

General information

Not available.

Eye/face protection

Safety glasses with side-shields conforming to EN 166.

Skin protection

- Hand protection

Protective gloves complying with EN 374. Glove permeation data does not exist for this material.

- Other

Not available.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the respirator. Use respirators and components tested and

approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Thermal hazards

Not available.

Hygiene measures

Use good industrial hygiene practices in handling this material.

When mixing and handling, use protective clothing, impervious gloves, and dust respirator. Operators should wash thoroughly with soap and water after handling. If accidental eye contact

occurs, immediately rinse with plenty of water.

In a manufacturing setting, wear chemical-resistant gloves and body covering to minimize skin contact. If handled in a ventilated enclosure, as in a laboratory setting, respirator and goggles or

face shield may not be required. Safety glasses are always required.

Environmental exposure

controls

Contain spills and prevent releases and observe national regulations on emissions. Inform

appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid.

Form Colour

Light yellow...

Odour

Musty.

Odour threshold

No data available.

Melting point/freezing point

No data available.

Initial boiling point and

No data available.

iniciai boiling

No data available.

boiling range Flash point

No data available.

Evaporation rate

No data available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower No data available,

(%)

Flammability limit -

No data available.

upper (%)

Explosive limit - lower

No data available.

(%)

Explosive limit – upper

No data available.

(%)

Vapour pressure

No data available.

Vapour density Relative density No data available. No data available.

Solubility(ies)
Partition coefficient

No data available.

(n-octanol/water)

No data available.

Auto-ignition temperature

No data available.

Decomposition temperatureNo data available. **Viscosity**No data available. **Explosive properties**Not explosive

Explosive properties Not explosive **Oxidizing properties** No oxidizing properties.

9.2. Other information

DensityNo data available.FlammabilityNo data available.Minimum ignition
temperatureNo data available.

Percent volatile No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity Not water reactive,

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous Not av

reactions

Not available.

10.4. Conditions to avoid Avoid heat.10.5. Incompatible materials Not available.

10.5. Incompatible materials Not available **10.6. Hazardous** Hazardous

decomposition products

Hazardous decomposition products formed under fire conditions

SECTION 11: Toxicological information

General information Not available.

11.1. Information on toxicological effects

Components	Species	Test results	
Benzyl alcohol (CAS 100-51-6)			
Acute			
Inhalation			
LD50	Rat	> 4178 mg/m3, 4 hr	
Oral			
LD50	Rat	1620 mg/kg	
ENILCONAZOLE (CAS 35554-44-	0)		
Acute			
Dermal			
LD	Rat	> 2000 mg/kg	
Inhalation			
LC50	Rat	16 mg/l, 4 Hours	
Oral			
LD50	Rat	277 mg/kg	
Ethanol (CAS 64-17-5)			
Acute			
Dermal	0.11%		
LD50	Rabbit	> 5000 mg/kg	
Inhalation	2.1		
LC50	Rat	124,7 mg/l, 4 h	
Oral	D-4		
LD50	Rat	7060 mg/kg	
Skin corrosion/irritation	Irritating to skin.		
Serious eye damage/eye irritatlon	Causes serious eye irritation.		
Respiratory sensitisation	(Enilconazole) Not a sensitizer. Based on available data, the classification criteria are not met		
Skin sensitisation	Causes skin irritation.		
Germ cell mutagenicity	(Enilconazole) No effects identified in animal studies criteria are not met.	s. Based on available data, the classification	

Material name: Clinafarm Spray

Carcinogenicity

(Enilconazole) No effects identified in animal studies. Based on available data, the classification

criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethanol (CAS 64-17-5)

1 Carcinogenic to humans.

Reproductive toxicity

Due to lack of data the classification is not possible.

Specific target organ toxicity

- single exposure

Due to lack of data the classification is not possible.

Specific target organ toxicity

- repeated exposure

Due to lack of data the classification is not possible.

Aspiration hazard

Due to lack of data the classification is not possible.

Mixture versus substance

information

Not available.

Other information

Not available.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life with long lasting effects.

Components		Species	Test results
Benzyl alcohol (CAS 100-51-6	j)		
Acute			
Crustacea	EC50	Daphnia	360 mg/l, 48 hr
Other	EC50	Pseudokirchnerella subcapitata	2600 mg/l, hr
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	10 mg/l, 96 hr
ENILCONAZOLE (CAS 35554-	44- 0)		
Crustacea	EC50	Daphnia	3,5 ppm, 48 hours
Other	LC50	Rainbow trout	1,48 mg/l, 96 hours
Ethanol (CAS 64-17-5)			
Other	LC50	Rainbow trout	13 g/l, 96 hr
Acute			
Algae	EC50	Algae	1450 mg/l, 8 d
Crustacea	LC50	Daphnia	9,3 g/l, 48 hr
12.2. Persistence and degradability	No data i	s available on the degradability of this proc	duct.
12.3. Bioaccumulative potential	Not avail	able.	
Partition coefficient n-octanol/water (log Kow)		
Benzyi alcohol		1,1	
ENILCONAZOLE Ethanol		3,82 Test method : -0,31	not available., at pH 9,2

12.4. Mobility in soil

12.5. Results of PBT

Chemical Safety Assessment is not required for this substance.

and vPvB assessment

12.6. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal

methods/information

Do not allow this material to drain into sewers/water supplies. Confirm disposal procedures with environmental engineer and local regulations. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

ADR

14,1, UN number

UN1993

Material name: Clinafarm Spray

```
14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (Ethanol)
     пате
     14.3. Transport hazard class(es)
         Class
                                3
         Subsidiary risk
         Label(s)
         Hazard No. (ADR)
                                Not available.
         Tunnel restriction
                                Not available.
         code
     14.4. Packing group
                                III
     14.5. Environmental
                                Yes
     hazards
     14.6. Special precautions
                                Not available.
     for user
 RID
     14.1, UN number
                                UN1993
     14.2. UN proper shipping
                                FLAMMABLE LIQUID, N.O.S. (Ethanol)
    name
    14.3. Transport hazard class(es)
         Class
                                3
        Subsidiary risk
                                3
        Label(s)
    14.4. Packing group
                                III
    14.5. Environmental
                                Yes
    hazards
    14.6. Special precautions
                                Not available.
    for user
ADN
    14.1. UN number
                                UN1993
    14.2. UN proper shipping
                                FLAMMABLE LIQUID, N.O.S. (Ethanol)
    name
    14.3. Transport hazard class(es)
        Class
                                3
        Subsidiary risk
        Label(s)
                                3
    14.4. Packing group
                                \Pi
    14.5. Environmental
                                Yes
    hazards
    14.6. Special precautions
                                Not available.
    for user
IATA
    14.1. UN number
                                UN1993
    14.2. UN proper shipping
                                FLAMMABLE LIQUID, n.o.s. (Ethanol)
    name
    14.3. Transport hazard class(es)
        Class
                                3
        Subsidiary risk
                                3
        Label(s)
    14.4. Packing group
                                Ш
    14.5, Environmental
                                Yes
    hazards
   ERG Code
                                3P
   14.6. Special precautions
                               Not available.
   for user
   Other information
        Passenger and cargo
                                Forbidden.
       aircraft
       Cargo aircraft only
                                Forbidden.
IMDG
   14,1. UN number
                                UN1993
   14.2. UN proper shipping
                               FLAMMABLE LIQUID, n.o.s. (Ethanol), MARINE POLLUTANT
   name
   14.3. Transport hazard class(es)
       Class
                                3
```

Subsidiary risk Label(s) 14.4. Packing group Ш 14.5. Environmental hazards

Marine pollutant Yes

F-E, S-E

14.6. Special precautions

Not available.

for user

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Not available.

Code

ADN; ADR; IATA; IMDG; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone laver, Annex I

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed. Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Ethanol (CAS 64-17-5)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not listed.

National regulations

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

15.2. Chemical safety assessment

Chemical Safety Assessment is not required for this substance.

Material name: Clinafarm Spray

SDS EU

SECTION 16: Other information

List of abbreviations

Not available.

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

R10 Flammable. R11 Highly flammable,

R20/22 Harmful by inhalation and if swallowed.

R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R53 May cause long-term adverse effects in the aquatic environment.

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Lilly Lab Code

Health: 2 Fire: 1 Reactivity: 0

Revision information

Product and Company Identification: Alternate Trade Names

SECTION 2: Hazards identification: Response SECTION 2: Hazards identification: Prevention Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Transport Information: Product Shipping Name/Packing Group

SECTION 16: Other information: Disclaimer

GHS: Classification

Disclaimer

As of the date of issuance, we are providing available information relevant to the handling of this material in the workplace. All information contained herein is offered with the good faith belief that it is accurate. THIS MATERIAL SAFETY DATA SHEET SHALL NOT BE DEEMED TO CREATE ANY WARRANTY OF ANY KIND (INCLUDING WARRANTY OF MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE). In the event of an adverse incident associated with this material, this safety data sheet is not intended to be a substitute for consultation with appropriately trained personnel. Nor is this safety data sheet intended to be a substitute for product literature which may accompany the finished product.

For additional information contact:

Elanco Animal Health 00+1+317-276-2000 00+1-800-428-4441

Material name: Clinafarm Spray