

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/04/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Substance
Substance name	: Potassium Permanganate
CAS No	: 7722-64-7
Product code	: LC19850
Formula	: KMnO4
Synonyms	: permanganate of potash / potassium salt permanganic acid
BIG no	: 10297

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Oxidant Bleaching agent Reagent Disinfectant Deodorizer Algicide Dyestuff/pigment: component Medicine Laboratory chemical Food industry: additive Insecticide Germicide
------------------------------	--

#### 1.3. Details of the supplier of the safety data sheet

LabChem Inc  
Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court  
Zelienople, PA 16063 - USA  
T 412-826-5230 - F 724-473-0647  
[info@labchem.com](mailto:info@labchem.com) - [www.labchem.com](http://www.labchem.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Ox. Sol. 2	H272
Acute Tox. 4 (Oral)	H302
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

#### 2.2. Label elements

##### GHS-US labelling

##### Hazard pictograms (GHS-US)



GHS03

GHS07

GHS09

##### Signal word (GHS-US)

: Danger

##### Hazard statements (GHS-US)

: H272 - May intensify fire; oxidiser  
H302 - Harmful if swallowed  
H410 - Very toxic to aquatic life with long lasting effects

##### Precautionary statements (GHS-US)

: P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P220 - Keep/Store away from clothing, combustible materials  
P221 - Take any precaution to avoid mixing with combustibles  
P264 - Wash exposed skin thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P273 - Avoid release to the environment

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P312 - IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell  
P330 - If swallowed, rinse mouth  
P391 - Collect spillage  
P501 - Dispose of contents/container to comply with local, state and federal regulations

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Substance type : Mono-constituent

Name	Product Identifier	%	GHS-US classification
Potassium Permanganate (Main constituent)	(CAS No) 7722-64-7	100	Ox. Sol. 2, H272 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
- First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
- First-aid measures after skin contact : Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.
- First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Immediately consult a doctor/medical service. Call Poison Information Centre ([www.big.be/antigif.htm](http://www.big.be/antigif.htm)). Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects both acute and delayed

- Symptoms/injuries after inhalation : AFTER INHALATION OF DUST: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. EXPOSURE TO HIGH CONCENTRATIONS: Respiratory difficulties. FOLLOWING SYMPTOMS MAY APPEAR LATER: Risk of lung oedema.
- Symptoms/injuries after skin contact : Tingling/irritation of the skin. May stain the skin. ON CONTINUOUS EXPOSURE/CONTACT: Caustic burns/corrosion of the skin.
- Symptoms/injuries after eye contact : Corrosion of the eye tissue. Inflammation/damage of the eye tissue. ON CONTINUOUS EXPOSURE/CONTACT: Permanent eye damage.
- Symptoms/injuries after ingestion : Nausea. Vomiting. Diarrhoea. Irritation of the gastric/intestinal mucosa. AFTER ABSORPTION OF HIGH QUANTITIES: Possible esophageal perforation. Shock. Slowing heart action. Low arterial pressure. Possible laryngeal spasm/oedema. Respiratory difficulties.
- Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Respiratory difficulties. Impairment of the nervous system. Movement disturbances. Coordination disorders. Myasthenia. Tremor. Paralysis. Cramps/uncontrolled muscular contractions. Impaired memory. Emotional instability.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : EXTINGUISHING MEDIA FOR SURROUNDING FIRES: All extinguishing media allowed. Preferably: quantities of water.
- Unsuitable extinguishing media : No unsuitable extinguishing media known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Promotes combustion. Reactions involving a fire hazard: see "Reactivity Hazard".
- Explosion hazard : INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".
- Reactivity : Decomposes on exposure to temperature rise: oxidation which increases fire hazard. Reacts with combustible materials: risk of spontaneous ignition. Violent to explosive reaction with (some) acids: release of toxic and corrosive gases/vapours. Reacts violently with many compounds e.g.: with organic material and with (strong) reducers. With (some) metals. With (increased) risk of fire/explosion.

#### 5.3. Advice for firefighters

- Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation.
- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.
- Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Face-shield. Protective clothing. Dust cloud production: compressed air/oxygen apparatus. Dust cloud production: dust-tight suit. Reactivity hazard: compressed air/oxygen apparatus. Reactivity hazard: gas-tight suit.
- Emergency procedures : Mark the danger area. Prevent dust cloud formation. No naked flames. Keep containers closed. Wash contaminated clothes. In case of hazardous reactions: keep upwind. In case of reactivity hazard: consider evacuation.
- Measures in case of dust release : In case of dust production: keep upwind. Dust production: have neighbourhood close doors and windows.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Do not breathe dust.
- Emergency procedures : If a major spill occurs, all personnel should be immediately evacuated and the area ventilated. Stop release. Ventilate area.

#### 6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the solid spill. Knock down/dilute dust cloud with water spray. If reacting: dilute toxic gas/vapour with water spray. Take account of toxic/corrosive precipitation water.
- Methods for cleaning up : Stop dust cloud by covering with sand/earth. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Spill must not return in its original container. See "Material-handling" for suitable container materials. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep the substance free from contamination. Use corrosionproof equipment. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Avoid raising dust. Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2 Conditions for safe storage, including any incompatibilities

- Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: heat sources.
- Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials, reducing agents, (strong) acids, metal powders, cellulosic materials, organic materials, alcohols, peroxides.
- Storage area : Store at ambient temperature. Keep out of direct sunlight. Store in a dry area. Fireproof storeroom. Unauthorized persons are not admitted. Keep only in the original container. Store only in a limited quantity. Meet the legal requirements.
- Special rules on packaging : SPECIAL REQUIREMENTS: closing, clean, correctly labelled, meet the legal requirements. Secure fragile packagings in solid containers.
- Packaging materials : SUITABLE MATERIAL: steel, aluminium, glass, stoneware/porcelain. MATERIAL TO AVOID: wood, cellulosic material.

### 7.3 Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Potassium Permanganate (7722-64-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> as Mn

### 8.2 Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation.
- Materials for protective clothing : GIVE EXCELLENT RESISTANCE: polyethylene. GIVE GOOD RESISTANCE: butyl rubber, PVC, polyethylene/ethylenevinylalcohol.
- Hand protection : Gloves.
- Eye protection : Face shield. In case of dust production: protective goggles.
- Skin and body protection : Protective clothing. In case of dust production: head/neck protection. In case of dust production: dustproof clothing.
- Respiratory protection : Dust production: dust mask with filter type P3. High dust production: self-contained breathing apparatus.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Crystalline solid. Crystalline powder.
- Molecular mass : 158.03 g/mol
- Colour : Dark violet-brown.
- Odour : Odourless.
- Odour threshold : No data available
- pH : 7.0 - 8.5 (1.6 %)
- pH solution : 1.6 %
- Relative evaporation rate (butylacetate=1) : No data available
- Melting point : > 240 °C
- Freezing point : No data available
- Boiling point : Not applicable
- Flash point : Not applicable
- Self ignition temperature : Not applicable
- Decomposition temperature : > 240 °C
- Flammability (solid, gas) : No data available
- Vapour pressure : < 0.10 hPa
- Relative vapour density at 20 °C : No data available
- Relative density : 2.7
- Density : 2700 kg/m<sup>3</sup>

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: Moderately soluble in water. Substance sinks in water. Soluble in ethanol. Soluble in methanol. Soluble in acetone. Soluble in acetic acid. Soluble in sulfuric acid. Soluble in pyridine. Water: 6.4 g/100ml
Log Pow	: -1.73 (Estimated value)
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: May intensify fire; oxidiser.
Explosive limits	: No data available

### 9.2 Other information

Minimum ignition energy	: Not applicable
SADT	: Not applicable
VOC content	: Not applicable
Other properties	: Opaque. Substance has basic reaction.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Decomposes on exposure to temperature rise: oxidation which increases fire hazard. Reacts with combustible materials: risk of spontaneous ignition. Violent to explosive reaction with (some) acids: release of toxic and corrosive gases/vapours. Reacts violently with many compounds e.g.: with organic material and with (strong) reducers. With (some) metals. With (increased) risk of fire/explosion.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Reacts exothermically with combustible materials: (increased) risk of fire.

### 10.4 Conditions to avoid

Incompatible materials.

### 10.5 Incompatible materials

Strong reducing agents. Organic compounds. combustible materials. metals.

### 10.6 Hazardous decomposition products

manganese.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity : Harmful if swallowed.

#### Potassium Permanganate (lf)7722-84-7

LD50 oral rat	1090 mg/kg (Rat)
Skin corrosion/irritation	: Not classified pH: 7.0 - 8.5 (1.6 %)
Serious eye damage/irritation	: Not classified pH: 7.0 - 8.5 (1.6 %)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after inhalation	: AFTER INHALATION OF DUST: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. EXPOSURE TO HIGH CONCENTRATIONS: Respiratory difficulties. FOLLOWING SYMPTOMS MAY APPEAR LATER: Risk of lung oedema.
Symptoms/injuries after skin contact	: Tingling/irritation of the skin. May stain the skin. ON CONTINUOUS EXPOSURE/CONTACT: Caustic burns/corrosion of the skin.
Symptoms/injuries after eye contact	: Corrosion of the eye tissue. Inflammation/damage of the eye tissue. ON CONTINUOUS EXPOSURE/CONTACT: Permanent eye damage.
Symptoms/injuries after ingestion	: Nausea. Vomiting. Diarrhoea. Irritation of the gastric/intestinal mucosa. AFTER ABSORPTION OF HIGH QUANTITIES: Possible esophageal perforation. Shock. Slowing heart action. Low arterial pressure. Possible laryngeal spasm/oedema. Respiratory difficulties.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Respiratory difficulties. Impairment of the nervous system. Movement disturbances. Coordination disorders. Myasthenia. Tremor. Paralysis. Cramps/uncontrolled muscular contractions. Impaired memory. Emotional instability.
Likely routes of exposure	: Skin and eye contact; Inhalation

### SECTION 12: Ecological information

#### 12.1 Toxicity

Ecology - general	: Dangerous for the environment.
Ecology - air	: TA-Luft Klasse 5.2.2/III.
Ecology - water	: Severe water pollutant (surface water). Ground water pollutant. Toxic to fishes. Very toxic to invertebrates (Daphnia).

Potassium Permanganate (7722-84-7)	
LC50 fishes 1	0.261 mg/l (96 h; <i>Ictalurus punctatus</i> )
EC50 Daphnia 1	0.235 mg/l (24 h; <i>Daphnia magna</i> )
LC50 fish 2	1.22 mg/l 96 h; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> )
EC50 Daphnia 2	0.5 mg/l (96 h; Crustacea)
TLM fish 1	5.4 ppm (48 h; <i>Lepomis macrochirus</i> )
Threshold limit other aquatic organisms 1	> 0.64 mg/l (Plankton)
Threshold limit algae 1	10 mg/l (4 h; <i>Chlorella</i> sp.)

#### 12.2 Persistence and degradability

Potassium Permanganate (7722-84-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

#### 12.3 Bioaccumulative potential

Potassium Permanganate (7722-84-7)	
Log Pow	-1.73 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.

#### 12.4 Mobility in soil

No additional information available

#### 12.5 Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Waste disposal recommendations	: Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle/reuse. Immobilize the toxic or harmful components. Remove to an authorized dump (Class I).
Additional information	: LWCA (the Netherlands): KGA category 06. Hazardous waste according to Directive 2008/98/EC.

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1490 Potassium permanganate, 5.1, II  
UN-No.(DOT) : 1490  
DOT NA no. : UN1490  
DOT Proper Shipping Name : Potassium permanganate  
Department of Transportation (DOT) Hazard Classes : 5.1 - Class 5.1 - Oxidizer 49 CFR 173.128  
Hazard labels (DOT) : 5.1 - Oxidiser



Packing group (DOT) : II - Medium Danger  
DOT Special Provisions (49 CFR 172.102) : IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).  
IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle.  
IP4 - Flexible, fiberboard or wooden IBCs must be sift-proof and water-resistant or be fitted with a sift-proof and water-resistant liner.  
T3 - 2.65 178.274(d)(2) Normal..... 178.275(d)(2)  
TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 152  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 212  
DOT Packaging Bulk (49 CFR 173.xxx) : 240  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 25 kg  
DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.  
DOT Vessel Stowage Other : 56 - Stow "separated from" ammonium compounds, 58 - Stow "separated from" cyanides  
Marine pollutant : P



### Additional information

Other information : No supplementary information available.  
State during transport (ADR-RID) : as solid.

### ADR

Transport document description : UN 1490 Potassium permanganate, 5.1, II, (E)  
Packing group (ADR) : II

# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (ADR) : 5.1 - Oxidizing substances  
Hazard identification number (Kemler No.) : 50  
Classification code (ADR) : O2  
Danger labels (ADR) : 5.1 - Oxidizing substances



Orange plates : An orange rectangular label with a black border. The number '50' is in the top half and '1490' is in the bottom half, both in black text.

Tunnel restriction code : E

### Transport by sea

UN-No. (IMDG) : 1490  
Class (IMDG) : 5.1 - Oxidizing substances  
EmS-No. (1) : F-H  
EmS-No. (2) : S-Q

### Air transport

UN-No.(IATA) : 1490  
Class (IATA) : 5 - Oxidizing substances  
Packing group (IATA) : II - Medium Danger

## SECTION 15: Regulatory information

### 15.1 US Federal regulations

Potassium Permanganate (7722-84-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 311/312 Hazard Classes	Reactive hazard

### 15.2 International regulations

#### CANADA

Potassium Permanganate (7722-84-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class C - Oxidizing Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Ox. Sol. 2 H272  
Acute Tox. 4 (Oral) H302  
Aquatic Acute 1 H400  
Aquatic Chronic 1 H410

Full text of H-phrases: see section 16

### Classification according to Directive 67/548/EEC or 1999/45/EC

O; R8  
Xn; R22  
N; R50/53



# Potassium Permanganate

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of R-phrases: see section 16

### 15.2.2. National regulations

**Potassium Permanganate (7722-64-7)**

Listed on the Canadian Ingredient Disclosure List

### 15.3 US State regulations

No additional information available

## SECTION 16: Other information

Full text of H-phrases: see section 16:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Ox. Sol. 2	Oxidising Solids, Category 2
H272	May intensify fire; oxidiser
H302	Harmful if swallowed
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects


NFPA health hazard

NFPA fire hazard

NFPA reactivity

NFPA specific hazard

- : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- : 0 - Materials that will not burn.
- : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
- : OX - This denotes an oxidizer, a chemical which can greatly increase the rate of combustion/fire.



HMIS III Rating

Health

Flammability

Physical

Personal Protection

- : 1 Slight Hazard - Irritation or minor reversible injury possible
- : 0 Minimal Hazard
- : 0 Minimal Hazard
- : F

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.